

PRODUCT DATA SHEET

TOUCHÉ CONTROLS



KEYED SMART SWITCH



TWO KEYS
INCLUDED WITH
EACH SWITCH

DESCRIPTION

Keyed Smart Switches are SmartNet devices allowing the user to enable or force a room's state by use of a key. These switches are commonly used for lockout of normal operation but are also able to perform a timed lockout function or keyed manual operation. Multiple keyed switches can be connected, allowing them to share a state (3-way operation). A LED indicator on each switch provides visual feedback on the room's current state.

FEATURES

- All power and communication for this device originates from the room controller (Room Manager or SmartPack). Connection to this device is accomplished with a standard CAT5 cable like all other Touché Smart devices. Multiple switches can be interconnected for 3-way style operation.
- Switches fit into standard 1-gang electrical junction box configurations (4" Sq. Box with plaster ring or masonry box). Ganging of multiple switches can be done without any special rough-in considerations.
- The required faceplate (not included) is a standard Decora® wall-plate.
- Supports multiple mode configurations: lockout, timed lockout, and keyed manual.
- Available in five standard colors:



WHITE

LGT ALMOND

IVORY

GRAY

BLACK

Touché Controls (a Product of ESI Ventures)

A: 2085 Humphrey Street, Fort Wayne, IN 46803

T: 888-841-4356

W: ToucheControls.com

Doc: Rev1-1-22

SPECIFICATIONS

VOLTAGE	24VDC - SOURCED FROM SMARTNET (NO EXTERNAL POWER SUPPLY REQUIRED)
CONNECTIVITY	CAT5 (MINIMUM)
AMBIENT TEMPERATURE	60C (140F)
MAXIMUM HUMIDITY	10 - 90%, NON-CONDENSING

CATALOGUE NUMBER

DEVICE TYPE	FUNCTION	COLOR
SS Smart Switch	K Keyed	WHT White
		GRY Gray
		IV Ivory
		BLK Black
		LA Light Almond

MODES

- Lockout (Green Indication):**
 selected scene/preset is forced on and overrides any other manual or automatic control
- Timed Lockout (Red Indication):**
 selected scene/preset is forced on and overrides any other manual or automatic control for a pre-determined amount of time (1 - 8 hours).
- Keyed Manual (Blue Indication):**
 this mode mimics the operation of a single function switch (SS-SF) but uses the keyed momentary input from this device for control of the room.
- Reset/Off (No Indication):**
 holding the key in the on-state for more than 1 second resets the operation of the room to its normal mode.

CONNECTIVITY

